



Technical Specification

Technical Service Department,
JSP Ltd., Worsham Mill, Minster
Lovell, Oxford, OX29 0TA
Tel.: 01993 824000
Fax: 01993 824422

JSP Stealth 9000 Spectacle

Conformity:

Conforms to EN 166.
EC Certificate Number 726, issued by issued by
Inspec Certification Limited.

Performance:

Lens and frame offer protection against low energy high-speed particles at 45 m/s (101 mph). The optical qualities of the lens comply with the requirements of optical class 1 (highest).

Features:

- Full eye protection
- Co-injected temples to avoid slipping
- Bridge integral to frame
- Dual lens design with wraparound protection
- Maximum field of vision
- Soft nose pad releases the pressure from the nose
- Stylish temple design with soft tips offers snug fitting
- Lens filters 99.9% of harmful UV light
- Anti-scratch lens
- N Class Anti-fog lens available

Markings:

Frame:
EN166 1.F

Lens:

Lens Type	Standard	Marking	Marking Type
Amber/Clear	2 . 1.2		1.F.N
Indoor/Outdoor	5 . 1.7		1.F
Smoke/Blue Mirror	5 . 2.5		1.F



Sizes and Weight:

Component Property	Measurement
Lens Thickness	2.3mm
Lens Base	9.5mm curve
Weight	24g
Lens size (Vertical)	42mm
Lens size (Diagonal)	82mm
Bridge	14mm
Temple length (lens to tip)	158mm
Overall Width (hinge to hinge)	138mm
Closest point between temple tips	94mm

Materials:

Component	Materials
Lens	Polycarbonate
Frame	Polycarbonate
Temple	Polycarbonate TPR
Part	Polycarbonate
Nose Pad	PVC

Instructions for Use:

In use ensure that the safety spectacles fit comfortably and securely on the head. Ensure that the safety spectacles are in place, before entering the hazard area.

Limitations of Use:

Protection will only be offered if the safety spectacles are fitted correctly. If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately. Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer. The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eye shield and seek medical advice. The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.

Notes:

- These safety spectacles are not suitable for protection against dusts, liquids or molten metals*

Cleaning & Maintenance:

The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth. Do not clean with chemical or abrasive cleaners. The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.