

**C.S.A. Z195-14** 

HARD ROCK INSULATING line exceeds requirements fixed from the Canadian norm CSA for electrical resistance. Determination of Electric Shock Resistance to a potential of **20.000 V, 60 HZ, FOR A PERIOD OF 1 MIN**

**INSULATING SOLE**  
**from > 1000 MΩ** 

The bottom of the shoe, within some limits (no humidity, it does not concern the upper), offers electrical resistance against tension up to 1.000V - M Ω > 1.000



**ASTM 2413 - 11** 

HARD ROCK INSULATING line exceeds requirements electrical resistance (EH) in accordance with ASTM 2413 - 11 electric hazard - Voltage: **20.000 V** / 60 Hz - duration: 1 min. - requirement of the electrical flow lower than 1.0 mA.



**VOLT SB FO E P HRO**  
HRD055H  
39-47



**HERTZ SB FO E P HRO**  
HRD154T  
39-47



**FRANKLIN SB FO E P WRU HRO**  
HRD052T  
37-47



**EDISON SB FO E P CI HI WRU HRO**  
HRD060D  
37-47



**AMPERE SB FO E P CI HI WRU HRO**  
HRD037T  
39-47



**TESLA SB FO E P CI HI WRU WR HRO**  
HRD057E  
39-47

